

VolP SIP Phone

VIP – 254T / 254PT SIP Server Install Procedure



Copyright © PLANET Technology Corporation. All rights reserved.



Scenarios explain: SIP Proxy Mode

We're using the free SIP proxy server **FWD** & **EasyCall** to perform the calling party. Please refer to the following descriptions and insert proper SIP registration information into the VIP-254T for establish the voice communications.





You could set information of service domains in this page.

Realm 1 (Default)				
Active:	⊙On ○Off			
Display Name:	288925			
Line Number:	288925			
Register Name:	288925			
Register Password:				
Domain Server:	fwd.pulver.com			
Proxy Server:	fwd.pulver.com			
Outbound Proxy:				
Status:	Registered			

1

Realm 2				
Active:	⊙ On ⊖ Off			
Display Name:	655768]		
Line Number:	655768]		
Register Name:	655768]		
Register Password:	•••••			
Domain Server:	sip.easycall.pl]		
Proxy Server:	sip.easycall.pl]		
Outbound Proxy:]		
Status:	Registered			

After logging in the SIP Phone, Click the [SIP Settings -> Service Domain] to input your SIP account. Realm 1 (Default) Active : On Display Name: 288925 Line Number : 288925 Register Name: 288925 Register Password: xxxxxx Domain Server: fwd.pulver.com Proxy Server: fwd.pulver.com Realm 2 Active : On Display Name: 655768 Line Number : 655768 Register Name: 655768 Register Password: xxxxxx Domain Server: sip.easycall.pl Proxy Server: sip.easycall.pl



Realm 3		
Active:	⊙ On ⊖ Off	Realm 3
Display Name:	300	Active : On
Line Number:	300	Display Name: 300
Register Name:	300	Line Number : 300
Register Password:	•••	Register Name: 300
Domain Server:	210.66.155.70	Register Password: 123
Proxy Server:	210.66.155.70	Domain Server: 210.66.155.70
Outbound Proxy:		Proxy Server: 210.66.155.70
Status:	Registered	
After confir modificatio Please click button to a	2 ming the n you've done, t on the Submit pply settings.	This page inform user important information. Configure OK. You have to save and reboot the VoIP to effect those changes.





Reboot without saving



Realm 1 (Default)			
Active:	⊙ On ○ Off		You can see the Register
Display Name:	288925		Status in the Status item. If
Line Number:	288925	4	the item shows "Registered",
Register Name:	288925		then your Phone Adapter is
Register Password:	•••		registered to the ISP, you
Domain Server:	fwd.pulver.com		can make a phone call
Proxy Server:	fwd.pulver.com		direcly.
Outbound Proxy:			
Status:	Registered		

Note:

When Registered success, you can try dial **613**, connect to **FWD ECHO TEST**, to test the SIP communication.

Step 1. Pickup up the handset.

- Step 2. Press the keypad, input 613
- Step 3. You can hear around three times back tone.
- Step 4. Then you'll hear the echo test voice.



Switch the realm (Registration Proxy Server):

The SIP Phone can register to three different SIP Proxies at the same time. It can receive any one of different SIP accounts incoming call, and it can switch to any one SIP accounts for making calls through input the switch code.

Realm switch code:

- 1 * : Realm 1 ---- FWD
- 2 * : Realm 2 ---- EasyCall
- 3 * : Realm 3 ---- Planet PBX

For example:

1.From FWD switch realm to EasyCall

The default is Realm 1, Input the 2* (Follow by the * key) from keypad and hang up the handset. It will switch to Realm 2, and it can make the SIP calls via realm 2.

Step 1. Pick up the handset

- Step 2. Press the keypad, input the 2*
- Step 3. Hang up the handset (It will switch to EasyCall)
- Step 4. Pick up the handset
- Step 5. Press the keypad, and dial 00 + number of country



For example:

2. From EasyCall switch realm to PLANET IPX-2000

Just now have Realm at EasyCall account, Input the 3* from keypad and hang up the handset. It will switch to PLANET PBX, and it can make a sip calls via PLANET PBX.

Step 1. Pick up the handset
Step 2. Press the keypad, input the 3*
Step 3. Hang up the handset (It will switch to PLANET IPX-2000)
Step 4. Pick up the handset
Step 5. Press the keypad, input the 6666 (Voice Mail)

Note:

The mentioned parameters and network settings in this sample should be carefully modified to meet the real-world applications.







