

Peer to Peer call: Hotline setting

Hot line Basic Concept:

Any number set in Hot line field will be dialed by VoIP call automatically.

For FXS port case: When user picks up the phone, the gateway will dial the hot line number to internet by VoIP call.

For FXO port case: When the FXO off-hook (PSTN call coming or PBX extension ring in), the gateway will dial the hot line number to internet by VoIP call.

Scenario description: Peer to Peer direct call via SIP or H.323 mode

STEP 1: To set the outgoing call dial plan in gateway, for example the number “911” call to gateway which’s the IP address is 172.16.0.119.

Outgoing Dial Plan: (maximun 50 entries, maximun length of prefix digits is 16 digit, maximun length of number is 20 digit)

Item	Outgoing no.	Length of Number	Delete Length	Prefix no.	Destination IP/DNS	Operation
1	911	3 ~ 3	0	None	172.16.0.119	
	<input type="text"/>	<input type="text"/> ~ <input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	ADD
DELETE Outbound Dial Plan From <input type="text"/> To <input type="text"/>						

STEP 2: To set hot line number in Hot Line Setting

Hot Line Number Setting (Hotline Setting)	
Port 1 number	<input type="text" value="911"/>
Port 2 number	<input type="text" value="None"/>
Port 3 number	<input type="text" value="None"/>
Port 4 number	<input type="text" value="None"/>
Port 5 number	<input type="text" value="None"/>
Port 6 number	<input type="text" value="None"/>
Port 7 number	<input type="text" value="None"/>
Port 8 number	<input type="text" value="None"/>

STEP 3: When users pick up the phone (port1), the gateway will dial the “911” to the gateway (IP address:

172.16.0.119)

Scenario description: Register to SIP proxy server/H.323 Gatekeeper direct call

STEP 1: Let your VIP-GW register to SIP proxy or H.323 Gatekeeper server

STEP 2: To set hot line number in Hot Line Option

Hot Line Number Setting (Hotline Setting)

Port 1 number	<input type="text" value="911"/>
Port 2 number	<input type="text" value="None"/>
Port 3 number	<input type="text" value="None"/>
Port 4 number	<input type="text" value="None"/>
Port 5 number	<input type="text" value="None"/>
Port 6 number	<input type="text" value="None"/>
Port 7 number	<input type="text" value="None"/>
Port 8 number	<input type="text" value="None"/>

STEP 3: When users pick up the phone (port1), the gateway will dial the “911” to SIP proxy or H.323 Gatekeeper server (ITSP)

Scenario description: Register to SIP Proxy / H.323 Gatekeeper server and Peer to Peer direct call first

STEP 1: Let your VIP-GW register to SIP proxy or H.323 Gatekeeper server

STEP 2: To set the outgoing call dial plan in gateway, for example the “911” will call to gateway which’s the IP address is 172.16.0.119.

Outgoing Dial Plan: (maximun 50 entries, maximun length of prefix digits is 16 digit, maximun length of number is 20 digit)

Item	Outgoing no.	Length of Number	Delete Length	Prefix no.	Destination IP/DNS	Operation
1	911	3 ~ 3	0	None	172.16.0.119	<input type="button" value="DELETE"/>
	<input type="text"/>	<input type="text"/> ~ <input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="button" value="ADD"/>

Outbound Dial Plan From To



PLANET Technology Corporation

11F, No. 96, Min Chuan Road, Hsin Tien, Taipei, Taiwan, R.O.C.
Tel: 886-2-2219-9518 Fax: 886-2-2219-9528
Email: sales@planet.com.tw Web site: <http://www.planet.com.tw>
VoIP Gateway: vip.planet.com.tw

*Planet reserves the right to change specifications without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright (c) 2006 PLANET Technology Corp. All rights reserved*

STEP 3: To set hot line number in Hot Line Setting

Hot Line Number Setting (Hotline Setting)	
Port 1 number	911
Port 2 number	None
Port 3 number	None
Port 4 number	None
Port 5 number	None
Port 6 number	None
Port 7 number	None
Port 8 number	None

STEP 4: When users pick up the phone (port 1), the gateway will dial the “911” to the gateway which’s IP address 172.16.0.119.

Note: This call will not call to SIP Proxy or H.323 Gatekeeper server because of direct call first.



PLANET Technology Corporation

11F, No. 96, Min Chuan Road, Hsin Tien, Taipei, Taiwan, R.O.C.
Tel: 886-2-2219-9518 Fax: 886-2-2219-9528
Email: sales@planet.com.tw Web site: <http://www.planet.com.tw>
VoIP Gateway: vip.planet.com.tw

*Planet reserves the right to change specifications without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright (c) 2006 PLANET Technology Corp. All rights reserved*