

## SIP speed call setting

### Speed calls Concept:

Cut your phone number down to fewer digit dialing!

Life is moving fast - you've got to dial fast. Now you can with Speed Dial. Dial the people you call most with just dialing fewer digits instead of dialing the full phone number.

What's even better is that you can customize and manage your speed dial phone numbers in Dial Plan Setting on your gateway! Dial Plan allows you to set up to speed dial numbers that can be called with the fewer numbers.

### Scenario description A: User wants to dial any number instead of 810-any number

Outgoing Dial Plan: (maximun 50 entries, maximun length of prefix digits is 16 digit, maximun length of number is 20 digit)

Item	Outgoing no.	Length of Number	Delete Length	Prefix no.	Destination IP/DNS	Destination Port	Operation
1	x	2 ~ 15	0	810	sip.test.com	5060	
	<input type="text"/>	<input type="text"/> ~ <input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	ADD
<input type="button" value="DELETE"/> Outbound Dial Plan		From <input type="text"/> To <input type="text"/>					

**Note:** The destination IP address is the domain name of SIP proxy server

### Scenario description B: User wants to dial 86-1234567890 instead of 810-86-1234567890

Outgoing Dial Plan: (maximun 50 entries, maximun length of prefix digits is 16 digit, maximun length of number is 20 digit)

Item	Outgoing no.	Length of Number	Delete Length	Prefix no.	Destination IP/DNS	Destination Port	Operation
1	86x	3 ~ 15	0	810	sip.test.com	5060	
	<input type="text"/>	<input type="text"/> ~ <input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	ADD
<input type="button" value="DELETE"/> Outbound Dial Plan		From <input type="text"/> To <input type="text"/>					

**Note:** The destination IP address is the domain name of SIP proxy server

**Scenario description C: User wants to dial 888 instead of 810-861234567890**

**Outgoing Dial Plan: (maximun 50 entries, maximun length of prefix digits is 16 digit, maximun length of number is 20 digit)**

Item	Outgoing no.	Length of Number	Delete Length	Prefix no.	Destination IP/DNS	Destination Port	Operation
1	999	3 ~ 3	3	8100861234567890	sip.test.com	5060	
	<input type="text"/>	<input type="text"/> ~ <input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<b>ADD</b>
<b>DELETE</b> Outbound Dial Plan		From <input type="text"/> To <input type="text"/>					

**Note:** The destination IP address is the domain name of sip proxy server



**PLANET Technology Corporation**

11F, No. 96, Min Chuan Road, Hsin Tien, Taipei, Taiwan, R.O.C.  
 Tel: 886-2-2219-9518 Fax: 886-2-2219-9528  
 Email: [sales@planet.com.tw](mailto:sales@planet.com.tw) Web site: <http://www.planet.com.tw>  
 VoIP Gateway: [vip.planet.com.tw](http://vip.planet.com.tw)

*Planet reserves the right to change specifications without prior notice.  
 All brand names and trademarks are property of their respective owners.  
 Copyright (c) 2006 PLANET Technology Corp. All rights reserved*